



e-ISSN: 2278-8875  
p-ISSN: 2320-3765

# International Journal of Advanced Research

in Electrical, Electronics and Instrumentation Engineering

Volume 10, Issue 3, March 2021

**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA

**Impact Factor: 7.122**

9940 572 462

6381 907 438

ijareeie@gmail.com

www.ijareeie.com



# Covid Inhibitor Using IOT

S.Dhanalakshmi<sup>1</sup>, S.Dhiviyadharshini<sup>2</sup>, B.Kowsika<sup>3</sup>, K.A.Sree Janani<sup>4</sup>

Assistant Professor, Dept. of EEE, Velammal College of Engineering and Technology, Madurai, Tamil Nadu, India<sup>1</sup>

UG Student, Dept. of EEE, Velammal College of Engineering and Technology, Madurai, Tamil Nadu, India<sup>2</sup>

UG Student, Dept. of EEE, Velammal College of Engineering and Technology, Madurai, Tamil Nadu, India<sup>3</sup>

UG Student, Dept. of EEE, Velammal College of Engineering and Technology, Madurai, Tamil Nadu, India<sup>4</sup>

**ABSTRACT:** Coronavirus immensely affects the general public, the new limitation has been forced as the quantity of people groups are permitted in a specific room in open social events. To keep up friendly separating alongside friendly removing standard temperature check at doors of shopping centres and office is compulsory. In this task we fix a room where a particularly important safety measures are taken, we utilize a laser diode and collector to recognize the passage of an individual, when the IR sensor distinguishes the passageway of an individual it will check the temperature, if the temperature is not exactly the set temperature the individual is permitted to enter something else, the section is denied. Just a set number of individuals are permitted in the room. The permitted temperature in the room can be checked and shown utilizing an I2C Display., just put your hands under the sensor, the delicate IR vicinity sensor will naturally detect and administer some cleanser to help you and your family to avoid microbes and keep a solid life


**KEYWORDS:** COVID , Laser diode, Temperature check, I2C display , Gear motor, IR proximity sensor.

## I.INTRODUCTION

These days crown infection is a significant issue . As of now there is no medication except for the immunization which is found is in a testing stage. As this is an extreme assault in this world, individuals are experiencing Coronavirus infection. The crown illness isn't only a basic infection assault, it makes basic to people by tainting the respiratory framework. The infection sickness is vigorously spreading everywhere on the world, as the countries are attempting to screen and restrict the spread of infection everywhere on the country. . There is an exacting assessment wherever to control the spread of the illness. The emergency clinic and numerous specialists are serving to fix the influenced individuals and attempting to stop the spreading of the infection to the adjoining individuals. Regular internal heat level checking is the one of the best approach to distinguish a crown patient. There are numerous sorts of thermometers are accessible in market. The typical thermometer can gauge the temperature of a Coronavirus patient and furthermore get the opportunity of spreading the infection. In this extraordinary circumstance we can utilize the Contactless temperature finder. In contact temperature sensor we may spread the illness by manual observing and this gadget is exorbitant. Programmed hand sanitizer distributors can detect the hands under the spout to apportion the fluid sanitizer. It apportions the ideal measure of sanitizer naturally to get the hands rapidly perfect.. The infection is spreading from the human hand and mouth salivation. The mouth spread is controlled with the veil material and the human hand is constrained by the hand wash sanitizer. On the off chance that the attendant goes close to the Coronavirus positive patients to sedate them or during home confinement if relatives goes close to the positive patients , there is a high possibility of spreading the illness .So by utilizing Coronavirus guardian we can maintain a strategic distance from the opportunity of spreading of the infection and accordingly the tablets or some other food things can be conveyed to the patients with no contact.


## II. WORKING PRINCIPLE

This focuses on the proposed overall system including its main stages , hardware/software components the proposed algorithm and how the proposed system works .In contactless temperature detector, the power supply will be given to the rectifier the rectifier converts ac to dc voltage after that the voltage will be fed to the regulator ,the regulator limits the voltage .The voltage again fed into the microcontroller i.e consists of 16pins.will be coded depending on the information need to display on LCD. The information that will be displayed are the temperature of the person entering. If the person temperature is above 99 degree farad,the door will not be opened if the temperature is below 99 degree, the door will open.



**Fig.1.Block Diagram of Contactless Temperature Detector**

In Handsfree sanitizer we will be connecting IR proximity sensor’s output to the water pump motor .So, whatever object we keep infront of IR proximity sensor , there will be power supply to the motor and the motor runs. The motor has shaft when ever water enters in to the shaft the water will be pumped outside which is connected to the IR proximity sensor.




**Fig.2.Block Diagram of Handsfree Sanitizer**

### III. COMPONENTS DESCRIPTION

#### IR SENSOR

An infrared sensor is an electronic gadget, that produces to detect a few parts of the environmental factors. An IR sensor can gauge the warmth of an article just as identifies the movement. These sorts of sensors measure just infrared radiation, as opposed to discharging it that is known as a uninvolved IR sensor. Normally, in the infrared range, every one of the articles transmit some type of warm radiation. Dynamic infrared sensors both produce and identify infrared radiation .When an article approaches the sensor, the infrared light from the Drove reflects off of the item and is identified by the collector. Dynamic IR sensors go about as vicinity sensors, and they are usually utilized in snag identification frameworks, (for example, in robots).



#### TEMPERATURE SENSOR

The MLX90614 is an infrared thermometer for non-contact temperature estimations. Both the IR delicate thermopile finder chip and the sign molding ASIC are coordinated in something similar TO-39 can. Coordinated into the




MLX90614 are a low commotion intensifier, 17-piece ADC and amazing DSP unit subsequently accomplishing high exactness and goal of the thermometer



### AURDINO

The Arduino Uno R3 is a microcontroller board dependent on a removable, double inline-bundle (Plunge) ATmega328 AVR microcontroller. It has 20 computerized input/yield pins (of which 6 can be utilized as PWM yields and 6 can be utilized as simple data sources). ... The R3 is the third, and most recent, modification of the Arduino Uno. The Arduino Uno R3 is a microcontroller board dependent on a removable, double inline-bundle (Plunge) ATmega328 AVR microcontroller.



### LCD DISPLAY

At the core of the connector is a 8-Cycle I/O Expander chip – PCF8574. This chip changes over the I2C information from an Arduino into the equal information needed by the LCD show. Arduino LCD show undertakings will run out of pin assets effectively, particularly with Arduino Uno. Furthermore, it is additionally exceptionally muddled with the wire binding and association. This I2C 16x2 Arduino LCD Screen is utilizing an I2C correspondence interface. It implies it just requirements 4 pins for the LCD show: VCC, GND, SDA, SCL. It will save at any rate 4 computerized/simple pins on Arduino. All connectors are standard XH2.54 (Breadboard type). You can associate with the jumper wire straightforwardly






## MOTOR DRIVER


The L293D is a famous 16-Pin Engine Driver IC. As the name proposes it is for the most part used to drive engines. A solitary L293D IC is fit for running two DC engines simultaneously; likewise the bearing of these two engines can be controlled freely

The L293D IC gets signals from the microchip and communicates the overall sign to the engines. It has two voltage pins, one of which is utilized to draw current for the working of the L293D and the other is utilized to apply voltage to the engines.



## GEAR MOTOR

Stuff engines are systems that change the speed of electric engines, driving them to work at a specific speed. They are made out of a progression of cog wheels that make up a kinematic chain, chipping away at a bunch of rotational parts. An equipped engine is a segment whose instrument changes the speed of the engine, driving them to work at a specific speed.



## IV. RESULT &CONCLUSION

Our outcomes show that temple infrared temperature control is a proper instrument to evaluate for irresistible infection straightforwardly at the passage of a structure, Programmed Hand Wash Gadget for Sterilization is productive and the expense cost is limited. It works like the ordinary contactless programmed machine. The human gets the restricted sanitizer fluid for disinfection close by, to wash the hands and to shield themselves from the crown sickness. Simultaneously it is climate amicable as in light of the fact that the dispensable wastage is insignificant, since it tends



to be topped off effectively with no specialized help. By utilizing Coronavirus guardian we can evade the spreading of the infection without direct contact we can secure our family ,companions and society.



## V. CONCLUSION

To maintain social distance and temperature measurement automatically without the help of human being CONTACTLESS TEMPERATURE DETECTOR senses the body temperature, when no one is measuring the measured shows the ambient temperature .The human gets the limited sanitizer liquid for sanitation in hand, to wash the hands and to protect themselves from the corona disease COVID CAREGIVER we can avoid the spreading of the virus without direct contact we can protect our family, friends and society Automatic Hand Wash Dispenser for Sanitation is efficient and the cost price is minimized. It works like the normal contactless automatic machine. The human gets the limited sanitizer liquid for sanitation in hand, to wash the hands and to protect themselves from the corona disease. At the same time it is environment friendly as because the disposable wastage is very minimal, since it can be refilled easily without any technical assistance by using COVID caregiver we can avoid the spreading of the virus without direct contact we can protect our family, friends and society.

## VI. FUTURE SCOPE


In future this device can be fabricated in a compact size so that is globally acceptable By implementing this method in schools , colleges, theatres, malls and super markets etc.. under influence of COVID INHIBITOR many diseases and fatalities can be minimized to large extent. As per Tamil Nadu relaxation people started to do their daily routine works but now Tamil Nadu Government is going to announce severe lockdown again due to vast increase in COVID cases. So, this project helps in preventing the spreading of the virus This project not only helps to prevent COVID cases but also it helps in preventing spreading of micro germs and other temperature related disease.

## REFERENCES

- [1]Francois A. Padovani, Westwood, Mass.; Tim H. McMains, Lexington; Michell R. Rowlette, Berea, both proposed a methodology on the topic TEMPERATURE SENSOR. A temperature sensor is an electronic device that measures the temperature of its environment and converts the input data into electronic data to record, monitor, or signal temperature changes. There are many different types of temperature sensors, Dec. 13, 1994 .
- [2]P. Wallace, Y. Yang, M. Campbell, Application of sol–gel processes for TEMPERATURE DETECTOR, Proc. 10th Opt. Fiber Sensors Conf., SPIE (1994), vol. 2360, p. 465.
- [3]S.A. Wade, E. Maurice, B.P. Petreski, S.F. Collins, G.W. Baxter, Proc. 20th Australian Conf. on .NON CONTACT TRANSDUCER VOL 19, pp. 331–334.
- [4]SRDJAN JOVANOVIC WEISS and SZE TSUNG LEONG proposed a methodology on the topic ELEVATOR Escalators are mechanical devices used for transporting people vertically between different levels of buildings. Typically, they take the form of a moving staircase, consisting of a 'chain' of single-piece aluminium or stainless steel steps guided by a system of tracks in a continuous loop,9th DEC 1859.



- [5]Christine L.Williams proposed a topic ESCALATOR – Person who wants to go from one end to other end escalator can be used VOL.39 issue 3,1st august 2014.
- [6]Chen, Anthonyproposed a model on ESCALATOR for travelling in the airports VOL 26 issue 5, 3rd September 2015 .
- [7]Akshay Sharma A S proposed a methodology on the topic AUTOMATIC HAND SANITIZER - An automatic hand sanitizer dispensing machine is automated, non contact, alcohol based hand sanitizer dispenser, which finds it's use in hospitals, work places, offices, schools and much more Vol. 9 Issue 07, July-2020
- [8]Gottman, J.M. & Krokoff, L.J. (1989). Proposed a methodology on the topic of HAND SANITIZER ,VOL 5 ,ISSUE 6,22nd MARCH 1997. [9]Wang C, Horby PW, Hayden FG, Gao GF proposed a methodology on the topic AUTOMATIC HANDSANITIZER - Hand sanitizers reduce levels of microorganisms by killing them chemically, just like disinfectants kill germs on environmental surfaces, 13th July 2020.



**INNO**  **SPACE**  
SJIF Scientific Journal Impact Factor

**Impact Factor:**  
**7.122**

**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
**INDIA**



# **International Journal of Advanced Research**

**in Electrical, Electronics and Instrumentation Engineering**

 **9940 572 462**  **6381 907 438**  **ijareeie@gmail.com**



[www.ijareeie.com](http://www.ijareeie.com)

Scan to save the contact details